

Information about Installation Environment for ixi-UMS

E-Mail: sales@estos.de Fax: +49 8142 479940

The following information is helpful for estos in terms of preparing/planning the installation:

Customer Data:

Company:

City:

CDP/CSP in charge of:

Customer Environment:

Mailserver/Groupware:

- ☐ Exchange Server 2016/2019
☐ Exchange Server 2013
☐ Exchange Server 2010
☐ IBM Domino
☐ Novell GroupWise
☐ Others:

Mail client at the workstations:

- ☐ Microsoft Outlook
☐ Microsoft Entourage
☐ IBM Notes
☐ Others:

Available PBX:

If you like to connect more than one PBX/Gateway please use the last page

Manufacturer:

Typ:

Release/Version:

Available user administration:

- ☐ Active Directory ☐ Domino Address Boo
☐ OpenLDAP ☐ Directory / NDS
☐ Others:

Client environment:

- Windows ☐ 10 ☐ 8.1 ☐ 8 ☐ 7
☐ 2008/2008 R2 ☐ 2012/2012 R2 ☐ 2016/201!
☐ Windows Terminal Server
☐ Citrix MetaFrame/Presentation Server
☐ Published Application ☐ Published Desktop
☐ Others:

Connection to ERP/data bases:

- ☐ SAP-System
☐ Others:

Special Features / Comments:

Information about Installation Environment for ixi-UMS

E-Mail: sales@estos.de Fax: +49 8142 479940

Information about the Planned Installation

Operating system for the ixi-UMS Server: ☐ Server 2016/2019 ☐ Windows 10 ☐ Server 2012/2012R2 ☐ Windows 8.x ☐ Server 2008/2008R2 ☐ Windows 7 Special Features ☐ VMWare ☐ Microsoft Virtual Server ☐ XenServer ☐ Microsoft Hyper-V ☐ Others: _____	Which UMS services shall be installed? ☐ Fax ☐ SMS ☐ Voice ☐ Mobile (up to v. 6.60) ☐ TTS ☐ MWI ☐ Auto Attendant ☐ MDS ☐ MultiSite Number of Sites: _____ ☐ several server Number of servers: _____ Number of Channels: _____
Which document types shall be sent as fax? ☐ Office, z.B. docx, xlsx ☐ PDF ☐ Others: _____	User administration for IXI-UMS: ☐ in the customer environment ☐ ixi-Framework Open LDAP Number of ixi-UMS users: _____
Connection of ixi-UMS to PBX: by ISDN: ☐ S ₀ ☐ S _{2M} Planned protocol properties: ☐ Point-to-Multipoint ☐ Point-to-Point ☐ DSS1 ☐ QSIG by VoIP: ☐ H.323 ☐ SIP Planned protocol properties: ☐ T.38 ☐ Softfax	Suitable ISDN hardware for the server is available: ☐ ISDN Board Typ: _____ ☐ Virtuelle CAPI Typ: _____ ☐ bintec elmeg Router Typ: _____ ☐ VoIPconnect from estos in use (SIP/H.323) ☐ Other standard CAPI-based VoIP connection in use / provided by the customer / third party product

For the installation, a server-suitable machine with Windows operating system is available at the customer's site.
 Are there any further applications/tools installed on this machine?

☐ No ☐ Yes. Installed applications/tools:

Information about Installation Environment for ixi-UMS

E-Mail: sales@estos.de Fax: +49 8142 479940

Special Features / Further Information about the Planned Installation / Comments

Who filled out this form?

First name:		surname:	
Company:		Dep/Position:	
E-mail:		Phone:	

The information stated above is correct .

Date:

Name / Signatur

estos products can be operated in various environments in flexible constellations. Please note that the information stated above represent a rough overview of the essential conditions at the customer's site. For the installation of the single components, the respective installation requirements according to estos's manufacturer documentations about the ixi-UMS Software and estos's terms and conditions are valid

Information about Installation Environment for ixi-UMS

E-Mail: sales@estos.de Fax: +49 8142 479940

For information with binding of several locations and/or pPBX

With binding of several locations and/or phone arrangements to the ixi-UMS system additional information is necessary:

Generall informationen about PBX System

☐ All PBX are linked up with each other All incoming calls can be reroute to one central PBX ☐ Ja ☐ Nein Alle ausgehenden Rufe gehen über den selben Amtskopf/Standort raus: ☐ Ja ☐ Nein If both questions with "Yes" were answered, only the data are required to the central phone arrangement (page 1)	☐ Die Telefonanlagen sind nicht vernetzt All PBX can be connected from ixi-UMS via ISDN ☐ Ja ☐ Nein All PBX can be connected from ixi-UMS via V ☐ Ja ☐ Nein The locations are connected with the central location by means of stable VPN connection (and free range) ☐ Ja ☐ Nein
---	--

PBX on location 2:

Manufacturer Typ:

Release/Version:

Connection of ixi-UMS to PBX

by ISDN: ☐ S₀ ☐ S_{2M} ☐ Point-to-Multipoint ☐ Point-to-Point

by VoIP: ☐ H.323 ☐ SIP ☐ T.38 ☐ Softfax

PBX on location 3:

Manufacturer Typ:

Release/Version:

Connection of ixi-UMS to PBX

per ISDN: ☐ S₀ ☐ S_{2M} ☐ Point-to-Multipoint ☐ Point-to-Point

per VoIP: ☐ H.323 ☐ SIP ☐ T.38 ☐ Softfax

Should other phone arrangements / locations be bound, give please the data questioned on top by e-mail.